

## PvBlack X890B

### 特种炭黑 Special carbon black

#### 简介 introduction:

特种炭黑 PvBlack X890B 设计用于 PP、PBT、PPS、LCP、ASA、PA 等工程改性塑胶的着色。对以上提供高黑度、蓝相, 高分散, 高纯度。Special carbon black PvBlack X890B is designed for the coloring of engineering modified plastics such as PP, PBT, PPS, LCP, ASA and PA. The above provides high blackness, blue phase, high dispersion, high purity.

理化性质 Physical and Chemical Properties	参数 parameter
外观 Appearance	细砂粒 Fine sand
平均原生粒径 Average original particle size (nm)	15±1
BET 比表面积 BET Specific surface area (m <sup>2</sup> /g)	270±10
DBP 吸油值 DBP Oil Absorption (cc/100g)	90±5
相对着色, IRB#3(%) Tinting Strength	145±5
挥发份 Volatile matter (%)	1.0±1
PH 值	8.5±0.5

#### 应用与特性 Application and characteristics:

- ◆ 高黑度 High blackness
- ◆ 蓝相 blue phase
- ◆ 高分散性 High dispersion
- ◆ 高纯度 High purity

#### 推荐应用 Recommended application:

用于不易着色的工程塑胶

For engineering plastics that are not easily colored

包装 packing: 20KG/Bag

备注: 本数据资料的提供出于诚意, 仅供参考, 需要由您自己测试并决定是否适合您的用途, 对我们产品的应用和处理以及您制造的最终产品都处于我们的控制之外, 我们无法承担保证和义务。

PS: The Data above is provided in good faith, FYI.

工厂地址: 新疆胡杨河市胡杨经济技术开发区车排子西路 3 号

公司地址: 东莞市常平镇桥沥南北路 25 号

电话: +86 (0) 755 23246611; 13510821649

传真: +86 (0) 755 29467129

邮箱: texong@163.com 网址: www.texong.com